

Safety Data Sheet acc. to OSHA HCS

Date of issue: 01/28/2025

Reviewed on 01/28/2025

1 Identification

Product identifier

Trade name: The Drying Agency 007

Other means of identification

Product Code: QW-0402

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Quest Car Care Products
3331 80th Avenue
Zeeland, MI 49464
USA

Information department: Chemical Department

Emergency telephone number:

Chemtrec
631404
1-800-424-9300 (24 hours)
1-703-527-3887 (24 hours (international))

2 Hazard(s) identification

Classification of the substance or mixture



GHS05 Corrosion

Eye damage 1

H318 Causes serious eye damage.



GHS07

Acute toxicity - oral 4

H302 Harmful if swallowed.

Acute toxicity - inhalation 4

H332 Harmful if inhaled.

Skin irritation 2

H315 Causes skin irritation.

Label elements

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



GHS05 GHS07

Signal word Danger

Hazard-determining components of labeling:

2-Butoxyethanol

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/28/2025

Reviewed on 01/28/2025

Trade name: The Drying Agency 007

(Contd. of page 1)

Alcohol Ethoxylated
QUATERNARY AMMONIUM COMPOUND
Aminomethoxysilane

Hazard statements

Harmful if swallowed or if inhaled.

Causes skin irritation.

Causes serious eye damage.

Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves / eye protection / face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If on skin: Wash with plenty of water.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Rinse mouth.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards**Results of PBT and vPvB assessment****PBT:**

	Proprietary Siloxane
	Proprietary Siloxane
556-67-2	Octamethylcyclotetrasiloxane

vPvB:

	Proprietary Siloxane
	Proprietary Siloxane
556-67-2	Octamethylcyclotetrasiloxane

Classification according to (d)(1)(ii) of § 1910.12000

The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.

Hazards not otherwise classified

There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

Substances:

111-76-2	2-Butoxyethanol	10-30%
	QUATERNARY AMMONIUM COMPOUND	10-30%
	Alcohol Ethoxylated	1-10%

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/28/2025

Reviewed on 01/28/2025

Trade name: The Drying Agency 007

(Contd. of page 2)

	Aminomethoxysilane	1-10%
107-41-5	2-Methylpentane-2,4-diol	1-10%
	Proprietary Siloxane	1-10%
	Proprietary Siloxane	1-10%
556-67-2	Octamethylcyclotetrasiloxane	1-10%

4 First-aid measures

Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Immediately call a doctor.

Most important symptoms and effects, both acute and delayed No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents: Use fire fighting measures that suit the environment.

Special hazards arising from the substance or mixture No further relevant information available.

Advice for firefighters

Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

US

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/28/2025

Reviewed on 01/28/2025

Trade name: The Drying Agency 007

(Contd. of page 3)

7 Handling and storage

Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

Information about protection against explosions and fires: No special measures required.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep receptacle tightly sealed.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Control parameters

Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

111-76-2 2-Butoxyethanol

PEL Long-term value: 240 mg/m³, 50 ppm

Skin

REL Long-term value: 24 mg/m³, 5 ppm

Skin

TLV Long-term value: 20 ppm

BEI, A3

107-41-5 2-Methylpentane-2,4-diol

REL Ceiling limit value: 125 mg/m³, 25 ppm

TLV Short-term value: 10** mg/m³, 50* ppm

Long-term value: 25* ppm

*vapor **inh. fraction, aerosol only

556-67-2 Octamethylcyclotetrasiloxane

WEEL Long-term value: 10* ppm

*OARS WEEL

Ingredients with biological limit values:

111-76-2 2-Butoxyethanol

BEI 200 mg/g creatinine

Medium: urine

Time: end of shift

Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Appropriate engineering controls No further data; see section 7.

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/28/2025

Reviewed on 01/28/2025

Trade name: The Drying Agency 007

(Contd. of page 4)

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:


Tightly sealed goggles

9 Physical and chemical properties

Information on basic physical and chemical properties
General Information

Physical state	Fluid
Color:	Amber colored
Odor:	Characteristic
Odor threshold:	Not determined.
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)
Flammability:	Not applicable.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	Not applicable.
Decomposition temperature:	Not determined.
pH-value at 20 °C (68 °F):	4-5
Viscosity:	
Kinematic:	Not determined.
Dynamic:	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible.
Partition coefficient (n-octanol/water):	Not determined.

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/28/2025

Reviewed on 01/28/2025

Trade name: The Drying Agency 007

(Contd. of page 5)

Vapor pressure:	Not determined.
Vapor pressure:	
Density at 20 °C (68 °F):	0.949 g/cm ³ (7.91941 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Particle characteristics	Not applicable.

Other information**Appearance:****Form:**

Liquid

Important information on protection of health and environment, and on safety.**Ignition temperature:**

Product is not selfigniting.

Danger of explosion:

Product does not present an explosion hazard.

Solvent separation test**Solids content:**

0.0 %

Change in condition**Evaporation rate**

Not determined.

10 Stability and reactivity

Reactivity No further relevant information available.**Chemical stability****Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.**Possibility of hazardous reactions** No dangerous reactions known.**Conditions to avoid** No further relevant information available.**Incompatible materials:** No further relevant information available.**Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects**Acute toxicity:****LD/LC50 values that are relevant for classification:****ATE (Acute Toxicity Estimate)**

Oral	LD50	966–1,021 mg/kg
Dermal	LD50	3,667–3,704 mg/kg
Inhalative	LC50/4 h	5–5.05 mg/l

111-76-2 2-Butoxyethanol

Oral	LD50	1,200 mg/kg (ATE) 1,480 mg/kg (rat)
Dermal	LD50	400 mg/kg (rab)
Inhalative	LC50/4 h	3 mg/l (ATE)

Alcohol Ethoxylated

Oral	LD50	1,400 mg/kg (rat)
------	------	-------------------

107-41-5 2-Methylpentane-2,4-diol

Oral	LD50	3,700 mg/kg (rat)
------	------	-------------------

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/28/2025

Reviewed on 01/28/2025

Trade name: The Drying Agency 007

(Contd. of page 6)

Dermal	LD50	8,560 mg/kg (rabbit)
556-67-2 Octamethylcyclotetrasiloxane		
Oral	LD50	1,540 mg/kg (rat)
Dermal	LD50	759 mg/kg (rabbit)
Inhalative	LC50/4 h	36 mg/l (rat)

Primary irritant effect:**on the skin:** Irritant to skin and mucous membranes.**on the eye:** Strong irritant with the danger of severe eye injury.**Sensitization:** No sensitizing effects known.**Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

Interactive effects No interactive effects between components are known.**Carcinogenic categories****IARC (International Agency for Research on Cancer)**

111-76-2	2-Butoxyethanol	3
----------	-----------------	---

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

Alternative sources for toxicological information

No non-standard sources for toxicological information where used.

12 Ecological information

Toxicity**Aquatic toxicity:** No further relevant information available.**Persistence and degradability** No further relevant information available.**Bioaccumulative potential** No further relevant information available.**Mobility in soil** No further relevant information available.**Results of PBT and vPvB assessment****PBT:**

	Proprietary Siloxane
	Proprietary Siloxane
556-67-2	Octamethylcyclotetrasiloxane

vPvB:

	Proprietary Siloxane
	Proprietary Siloxane
556-67-2	Octamethylcyclotetrasiloxane

Other adverse effects**Additional ecological information:****General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/28/2025

Reviewed on 01/28/2025

Trade name: The Drying Agency 007

(Contd. of page 7)

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

13 Disposal considerations

Waste treatment methods

Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number DOT, IMDG, IATA	not regulated
UN proper shipping name DOT, IMDG, IATA	not regulated
Transport hazard class(es) DOT, ADN, IMDG, IATA Class	not regulated
Packing group DOT, IMDG, IATA	not regulated
Environmental hazards:	Not applicable.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Special precautions for user	Not applicable.
UN "Model Regulation":	not regulated

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

Sara

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

111-76-2 2-Butoxyethanol

TSCA (Toxic Substances Control Act):

7732-18-5	water, distilled, conductivity or of similar purity	ACTIVE
111-76-2	2-Butoxyethanol	ACTIVE
	QUATERNARY AMMONIUM COMPOUND	ACTIVE
	Alcohol Ethoxylated	ACTIVE
107-41-5	2-Methylpentane-2,4-diol	ACTIVE

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/28/2025

Reviewed on 01/28/2025

Trade name: The Drying Agency 007

(Contd. of page 8)

64-19-7	acetic acid	ACTIVE
	Proprietary Siloxane	ACTIVE
	Proprietary Siloxane	ACTIVE
556-67-2	Octamethylcyclotetrasiloxane	ACTIVE

Hazardous Air Pollutants

None of the ingredients is listed.

Proposition 65
Chemicals known to cause cancer:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Carcinogenic categories
EPA (Environmental Protection Agency)

111-76-2	2-Butoxyethanol	NL
----------	-----------------	----

TLV (Threshold Limit Value)

111-76-2	2-Butoxyethanol	A3
----------	-----------------	----

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms


GHS05 GHS07

Signal word Danger

Hazard-determining components of labeling:

2-Butoxyethanol

Alcohol Ethoxylated

QUATERNARY AMMONIUM COMPOUND

Aminomethoxysilane

Hazard statements

Harmful if swallowed or if inhaled.

Causes skin irritation.

Causes serious eye damage.

Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves / eye protection / face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/28/2025

Reviewed on 01/28/2025

Trade name: The Drying Agency 007

(Contd. of page 9)

If on skin: Wash with plenty of water.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Rinse mouth.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Date of previous version 01/28/2025

Date of preparation 01/28/2025

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Acute toxicity - oral 4: Acute toxicity – Category 4

Skin irritation 2: Skin corrosion/irritation – Category 2

Eye damage 1: Serious eye damage/eye irritation – Category 1

*** Data compared to the previous version altered.**