

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.16.2023 Page 1 of 16

Revision date: 10.02.2023

Chem-Genie® 100

SECTION 1: Identification

Product Identifier

Product Name: Chem-Genie® 100

Product code: CG-100

Recommended Use of the Product and Restriction on Use

Relevant Identified Uses: Acidic Commercial Car Wash Detergent

Uses Advised Against: Not determined or not applicable.

Reasons Why Uses Advised Against: Not determined or not applicable.

Manufacturer or Supplier Details

Manufacturer: United States

Quest Car Care Products 3333 Production Ct. Zeeland, Michigan 49464 616-772-5100 www.questcarcare.com

www.questcarcare.com

Emergency Telephone Number:

United States

CHEMTREC

1-800-424-9300 (24 hrs)

1-800-262-8200 (24 hrs)

1-703-527-3887 (24 hrs (international))

SECTION 2: Hazard(s) Identification

GHS Classification:

Flammable liquids, category 4

Corrosive to metals, category 1

Acute toxicity (oral), category 4

Skin corrosion, category 1A

Serious eye damage, category ${\bf 1}$

Specific target organ toxicity - single exposure, category 3, respiratory tract irritation

Specific target organ toxicity - single exposure, category 3, narcotic effects

Aspiration hazard, category 1

Label elements

Hazard Pictograms:







Signal Word: Danger

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.16.2023 Page 2 of 16

Revision date: 10.02.2023

Chem-Genie® 100

Hazard statements:

H227 Combustible liquid

H290 May be corrosive to metals

H314 Causes skin burns and eye damage

H318 Causes serious eye damage

H302 Harmful if swallowed

H335 May cause respiratory irritation

H336 May cause drowsiness or dizziness if excessively inhaled

H304 May be fatal if swallowed and enters airways

Precautionary Statements:

P260 Do not breathe dust/fume/gas/mist/vapors/spray

P264 Wash hands/skin thoroughly after contact with or handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection

P270 Do not eat, drink or smoke when using this product

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P271 Use only outdoors or in a well-ventilated area

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking

P234 Keep only in original container

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P363 Wash contaminated clothing before reuse

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing P310 Immediately call a POISON CENTER/911/PHYSICIAN IF: swallowed, eye contact, skin burns/rash or breathing difficulties.

P321 Specific treatment (see first aid procedures on the product label in section 4 of this SDS)

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

P330 Rinse mouth

P312 Call a POISON CENTER/911/PHYSICIAN if you feel unwell.

P370+P378 In case of fire: Use water spray or foam to extinguish [water jet not recommended].

P390 Absorb spillage to prevent material-damage

P331 Do NOT induce vomiting

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/911 and follow first aid procedures on this SDS.

P405 Store locked up

P403+P233 Store in a well-ventilated place. Keep container tightly closed

P403+P235 Store in a well-ventilated place. Keep cool

P406 Store in corrosive resistant/or heavy duty plastic container using a chemical resistant inner liner.

P501 Dispose of contents/container in accordance with local, state and federal regulations.

Hazards Not Otherwise Classified: None

SECTION 3: Composition/Information on Ingredients

Identification	Name	Weight %
CAS Number: 7732-18-5	Water	20-40

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.16.2023 Page

Revision date: 10.02.2023

Chem-Genie® 100

CAS Number: 77-92-9	Citric acid	20-40
CAS Number: 68584-22-5	Benzenesulfonic acid, C10-16-alkyl derivatives	10-20
CAS Number: 111-76-2	2-Butoxyethanol	1-5
CAS Number: 64-17-5	Ethanol	1-5
CAS Number: 7664-93-9	Sulfuric acid	0.1-0.5

Additional Information:

Ingredients not listed above are being withheld as trade secret.

SECTION 4: First Aid Measures

Description of First Aid Measures

General Notes:

Show this Safety Data Sheet to the doctor in attendance. Take precautions to ensure your own safety before attempting rescue. Wear appropriate safety eyewear, gloves, protective clothing and respiratory protection to prevent exposure. See Section 8 of this SDS for personal protective equipment recommendations. Do not use the mouth to mouth method if victim has ingested or inhaled the product. Give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper device.

Show this Safety Data Sheet to the doctor in attendance.

After Inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

After Skin Contact:

Treatment is urgent. Seek emergency medical treatment. Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse.

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

After Eye Contact:

Immediately rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. Seek immediate medical attention, preferably from an ophthalmologist.

Rinse eyes with plenty of water for several minutes. Remove contact lenses, if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

After Swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. Seek

Page 3 of 16

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.16.2023

Revision date: 10.02.2023

Chem-Genie® 100

immediate medical attention.

This product presents an aspiration hazard. If aspiration is suspected, seek emergency medical treatment. If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most Important Symptoms and Effects, Both Acute and Delayed Acute Symptoms and Effects:

Exposure to skin may result in redness, pain, burning, inflammation and tissue damage. Exposure to eyes may result in irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision. Exposure via inhalation may result in cough, sore throat, burning sensation and shortness of breath. Exposure via ingestion may result in burns of the mouth and throat, abdominal pain, burning sensation in the throat and chest, nausea, vomiting, shock or collapse.

Eye contact may result in irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision.

Acute oral exposure may lead to dizziness, drowsiness, headache, breathing difficulties, nausea, vomiting, abdominal pain, and lowering of consciousness. Adverse effects are dependent on exposure (dose, concentration, contact time).

Inhalation may have adverse effects on the respiratory tract. Symptoms may include cough, breathing difficulties, sore throat and inflammation of the mucous membrane lining the respiratory tract.

Product is combustible. Exposure to sources of ignition may cause physical injury.

Products that are corrosive to metals are often corrosive to the skin, eyes and the respiratory tract. Inhalation may have adverse effects on the central nervous system. Symptoms may include drowsiness, dizziness, headache, nausea and lowering of consciousness. Acute overexposure via inhalation may result in respiratory distress, confusion and unconsciousness.

May be fatal if swallowed and enters airways. Aspiration may cause pulmonary edema and pneumonitis. Symptoms may include shortness of breath, dry cough and irritation of the nose, eyes, lips, mouth and throat.

Delayed Symptoms and Effects:

Effects are dependent on exposure (dose, concentration, contact time).

Symptoms of exposure may be delayed.

Symptoms of pulmonary edema may be delayed.

Immediate Medical Attention and Special Treatment

Specific Treatment:

In case of eye contact, seek prompt medical attention while rinsing is continued.

In case of skin contact, seek prompt medical attention while rinsing is continued.

In case of ingestion, seek prompt medical attention.

If respiratory symptoms persist, seek medical attention.

Skin/eye burns require immediate treatment.

Overexposure via inhalation requires urgent medical treatment.

Notes for the Doctor:

Treat symptomatically.

SECTION 5: Firefighting Measures

Extinguishing Media

Suitable Extinguishing Media:

Page 4 of 16

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.16.2023

Revision date: 10.02.2023

Chem-Genie® 100

Dry chemical, CO2, water spray or alcohol-resistant foam.

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Unsuitable Extinguishing Media:

Do not use water jet.

Specific Hazards During Fire-Fighting:

Combustible liquid. Will be easily ignitable by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation.

Contact with metals may evolve flammable hydrogen gas. Thermal decomposition may produce irritating/toxic fumes/gases.

Thermal decomposition may produce irritating/toxic fumes/gases.

Special Protective Equipment for Firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

Special precautions:

Evacuate non-essential personnel. Ventilate closed spaces before entering. Consider initial evacuation for 300 meters in all directions. If tank/rail car is involved in the fire, ISOLATE for 800 meters in all directions. Fight fire from a maximum distance. Move containers from fire area if you can do it without risk. Use water spray/fog for cooling fire exposed containers. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Always stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles. If this is impossible, withdraw from area and let fire burn. Stand by, at a safe distance, with extinguisher ready for possible re-ignition. A vapor-suppressing foam may be used to reduce vapors. Avoid unnecessary run-off of extinguishing media which may cause pollution. Do not handle damaged containers unless specialized to do so.

DO NOT GET WATER INSIDE CONTAINERS. Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

SECTION 6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. All equipment used when handling the product must be grounded. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling. Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Do not get on skin, eyes or on clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling. Remove contaminated clothing and launder before reuse.

Page 5 of 16

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.16.2023

Revision date: 10.02.2023

Chem-Genie® 100

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and Material for Containment and Cleaning Up:

Harmful if swallowed. Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Avoid breathing dust, mist, fumes, vapors or spray. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. A vapor-suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable corrosive resistant containers for future disposal. Do not get water in containers as reaction with water or moist air may release toxic, corrosive or flammable gases. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Reference to Other Sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and Storage

Precautions for Safe Handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Do not get in eyes. Avoid contact with skin and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating and lighting equipment. Take action to prevent static discharges. Handle containers with caution. Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Use appropriate personal protective equipment (see Section 8). Prevent skin contact. Do not get in eyes. Use only with adequate ventilation. Do not add water to the corrosive product. If it is necessary to mix a corrosive product with water, do so slowly adding the corrosive to cold water, in small amounts, and stir frequently. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use. Keep only in original packaging. Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not

Page 6 of 16

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.16.2023

Revision date: 10.02.2023

Chem-Genie® 100

in use.

Conditions for Safe Storage, Including Any Incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10). Store in cool, dry, well-ventilated location out of direct sunlight and away from exit paths. Store in a corrosion-resistant container with a resistant inner liner. Inspect containers and storage area regularly for signs of leak and damage. Store containers at a convenient height for handling, below eye level if possible. High shelving increases the risk of dropping containers, personal injury and exposure. Ensure that appropriate fire fighting and spill-clean up equipment is readily available. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Store separately. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure Controls/Personal Protection

Only those substances with limit values have been included below.

Occupational Exposure Limit Values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
OSHA	2-Butoxyethanol	111-76-2	8-Hour TWA-PEL: 240 mg/m ³ (50 ppm)
	Sulfuric acid	7664-93-9	8-Hour TWA-PEL: 1 mg/m ³
	Ethanol	64-17-5	8-Hour TWA-PEL: 1900 mg/m ³ ([1000 ppm])
NIOSH	2-Butoxyethanol	111-76-2	IDLH: 700 ppm
	2-Butoxyethanol	111-76-2	REL-TWA: 24 mg/m³ (5 ppm [up to 10 hr])
	Sulfuric acid	7664-93-9	REL-TWA: 1 mg/m³ (10 hr)
	Sulfuric acid	7664-93-9	IDLH: 15 mg/m³
	Ethanol	64-17-5	REL-TWA: 1900 mg/m³ (1000 ppm [up to 10 hr.])
	Ethanol	64-17-5	IDLH: 3300 ppm
ACGIH	2-Butoxyethanol	111-76-2	8-Hour TWA: 20 ppm
	Sulfuric acid	7664-93-9	8-Hour TWA: 0.2 mg/m³ (thoracic fraction)
	Ethanol	64-17-5	15-Minute STEL: 1000 ppm
United States(California)	2-Butoxyethanol	111-76-2	8-Hour TWA-PEL: 97 mg/m ³ (20 ppm)
	Sulfuric acid	7664-93-9	8-Hour TWA-PEL: 0.1 mg/m ³
	Sulfuric acid	7664-93-9	15-Minute STEL: 3 mg/m ³
	Ethanol	64-17-5	8-Hour TWA-PEL: 1900 mg/m ³ ([1000 ppm])
United States	2-Butoxyethanol	111-76-2	8-Hour TWA: 120 mg/m³ (25 ppm [U.S. State, Tennessee])

Biological Limit Values:

Page 7 of 16

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.16.2023 Page 8 of 16

Revision date: 10.02.2023

Chem-Genie® 100

Country (Legal Basis)	Substance	Identifi er	Determin ant		Sampling time	Permissibl e limits
ACGIH	2-Butoxyethanol		,	Creatinine in Urine	End of shift	200 mg/g

Information on Monitoring Procedures:

Not determined or not applicable.

Appropriate Engineering Controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal Protection Equipment

Eye and Face Protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Use safety glasses with side shields or goggles. Consider the use of a face shield for splash protection. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and Body Protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Full body protection should be worn. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory Protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

General Hygienic Measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.16.2023

Revision date: 10.02.2023

Chem-Genie® 100

before reuse. Perform routine housekeeping.

SECTION 9: Physical and Chemical Properties

Information on Basic Physical and Chemical Properties

Appearance	Viscous, Strawlike
Odor	Ether-like, Acrid
Odor threshold	Not determined or not available.
рН	1.0-2.0
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	60-93 c
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	1.05-1.10
Solubilities	Water
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

SECTION 10: Stability and Reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical Stability:

Stable under recommended handling and storage conditions.

Possibility of Hazardous Reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to Avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources, static electricity and incompatible materials. Vapor accumulation in low or confined areas.

Avoid generation of aerosols and mists, extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Incompatible Materials:

None known.

Page 9 of 16

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.16.2023

Revision date: 10.02.2023

Chem-Genie® 100

Hazardous Decomposition Products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological Information

Acute Toxicity

Assessment:

Harmful if swallowed.

Product Data: No data available.

Substance Data:

Name	Route	Result
2-Butoxyethanol	Dermal ATE	LD50 Rabbit: 1100 mg/kg
	Oral ATE	LD50 Rat: 1200 mg/kg
	Inhalation ATE	LC50 Rat: 3 mg/L (4 hr [Vapours])
Benzenesulfonic acid, C10-16-	inhalation	LC50 Rat: >1.9 mg/L (4 h [aerosol])
alkyl derivatives	Dermal ATE	LD50 Rabbit: 1100 mg/kg
	Oral ATE	LD50 Rat: 500 mg/kg
Sulfuric acid	oral	LD50 Rat: 2140 mg/kg
Ethanol	oral	LD50 Rat: 10,470 mg/kg
	inhalation	LC50 Rat: 116.9 mg/L (4 hr [vapor])
Citric acid	oral	LD50 Mouse: 5400 mg/kg
	dermal	LD50 Rat: > 2000 mg/kg

Skin Corrosion/Irritation

Assessment:

Causes severe skin burns and eye damage.

Product Data:

No data available.

Substance Data:

Name	Result
2-Butoxyethanol	Causes skin irritation.
Benzenesulfonic acid, C10-16-alkyl derivatives	Causes severe skins burns.
Sulfuric acid	Causes severe skin burns.

Serious Eye Damage/Irritation

Assessment:

Causes serious eye damage.

Product Data:

No data available.

Substance Data:

Name	Result
2-Butoxyethanol	Causes serious eye irritation.
Benzenesulfonic acid, C10-16-alkyl derivatives	Causes serious eye damage.
Sulfuric acid	Causes serious eye damage.

Page 10 of 16

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.16.2023

Revision date: 10.02.2023

Chem-Genie® 100

Name	Result
Ethanol	Causes serious eye irritation.
Citric acid	Causes serious eye irritation.

Respiratory or Skin Sensitization

Assessment: Based on available data, the classification criteria are not met.

Product Data:No data available.

Substance Data: No data available.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available. **Substance Data:** No data available.

International Agency for Research on Cancer (IARC):

Name	Classification
Sulfuric acid	Group 1
Water	Not Applicable
Ethanol	Not Applicable
Benzenesulfonic acid, C10-16-alkyl derivatives	Not Applicable
2-Butoxyethanol	Group 3
Citric acid	Not Applicable

National Toxicology Program (NTP):

Name	Classification
Sulfuric acid	Known to be human carcinogens
Water	Not Applicable
Ethanol	Not Applicable
Benzenesulfonic acid, C10-16-alkyl derivatives	Not Applicable
2-Butoxyethanol	Not Applicable
Citric acid	Not Applicable

OSHA Carcinogens: Not applicable

Germ Cell Mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:No data available.

Substance Data: No data available.

Reproductive Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:No data available.

Substance Data: No data available.

Specific Target Organ Toxicity (Single Exposure)

Assessment:

Page 11 of 16

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.16.2023

Revision date: 10.02.2023

Chem-Genie® 100

May cause respiratory irritation. May cause drowsiness or dizziness.

Product Data:No data available.

Substance Data:

Name	Result
Citric acid	May cause respiratory irritation.

Specific Target Organ Toxicity (Repeated Exposure)

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available. Substance Data:

Name	Result
	Repeated or prolonged inhalation may damage the lungs. Risk of tooth erosion upon repeated or prolonged exposure to an aerosol of this substance.

Aspiration toxicity

Assessment:

May be fatal if swallowed and enters airways.

Product Data:No data available.

Substance Data: No data available.

Information on Likely Routes of Exposure:

No data available.

Symptoms Related to the Physical, Chemical, and Toxicological Characteristics:

No data available. **Other Information:**No data available.

SECTION 12: Ecological Information

Acute (Short-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result
2-Butoxyethanol	Aquatic Invertebrates EC50 Daphnia magna: 1550 mg/L (48 hr [mobility])
	Fish LC50 Oncorhynchus mykiss: 1474 mg/L (96 hr)
	Aquatic Plants EC50 Raphidocelis subcapitata: 623 mg/L (72 hr [biomass])
Ethanol	Fish LC50 Pimephales promelas: 15,300 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: >10,000 mg/L (48 hr [mobility])
	Aquatic Plants EC50 Chlorella vulgaris: 275 mg/L (72 hr [growth rate])
	Bacteria LC50 Paramaecium caudatum: 5,800 mg/L (4 hr)

Page 12 of 16

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.16.2023

Revision date: 10.02.2023

Chem-Genie® 100

Name	Result
Sulfuric acid	Aquatic Plants EC50 Algae: >100 mg/L (72 hr [growth rate])
	Fish LC50 Lepomis macrochirus: >16 - <28 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: >100 mg/L (48 hr [mobility])
Citric acid	Fish LC50 Pimephales promelas: >100 mg/L (96 hr)
	Aquatic Invertebrates EC50 Dreissena polymorpha: >50 mg/L (48 hr [attachment to substrate])

Chronic (Long-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result
2-Butoxyethanol	Fish NOEC Danio rerio: > 100 mg/L (21 d [markers for endocrine disruptive effects])
	Aquatic Invertebrates NOEC Daphnia magna: 100 mg/L (21 d [reproduction])
Ethanol	Aquatic Invertebrates NOEC Daphnia Magna: 9.6 mg/L (10 d [reproduction])
	Fish NOEC Danio rerio: 250 mg/L (5 d)

Persistence and Degradability

Product Data: No data available.

Substance Data:

Name	Result
Benzenesulfonic acid, C10-16-alkyl derivatives	Under test conditions no biodegradation observed.
Citric acid	The substance is readily biodegradable. 97% degradation measured by CO2 evolution, after 28 days.
2-Butoxyethanol	The substance is readily biodegradable. 90.4% degradation, measured by CO2 evolution, after 28 days.
Ethanol	The substance is readily biodegradable. 84% degradation measured by O2 consumption, after 20 days.

Bioaccumulative Potential

Product Data: No data available.

Substance Data:

Name	Result
2-Butoxyethanol	The substance is not expected to bioaccumulate (log Kow = 0.83).
Ethanol	The substance is not expected to bioaccumulate in organisms (estimated BCF: 3).
Citric acid	The substance has low potential for bioaccumulation [BCF: 3.2 L/kg].

Mobility in Soil

Product Data: No data available.

Substance Data:

Name	Result
1	The substance is highly mobile; therefore, adsorption to soil is not expected (log Koc: 0.2).

Results of PBT and vPvB assessment

Page 13 of 16

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.16.2023

Revision date: 10.02.2023

Chem-Genie® 100

Product Data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT. **vPvB assessment:** This product does not contain any substances that are assessed to be a vPvB.

Substance Data:

PBT assessment:

2-Butoxyethanol	The substance is not PBT.
Sulfuric acid	PBT assessment does not apply to inorganic substances.
Ethanol	The substance is not PBT.
Citric acid	The substance is not PBT

vPvB assessment:

2-Butoxyethanol	The substance is not vPvB.
Sulfuric acid	vPvB assessment does not apply to inorganic substances.
Ethanol	The substance is not vPvB.
Citric acid	The substance is not vPvB

Other Adverse Effects: No data available.

SECTION 13: Disposal Considerations

Disposal Methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

Contaminated packages:

Not determined or not applicable.

SECTION 14: Transport Information

United States Transportation of Dangerous Goods (49 CFR DOT)

UN Number	3265
UN Proper Shipping Name	Corrosive, Liquid, Acidic, Organic, N.O.S. (Alkylbenzenesulfonic acid)
UN Transport Hazard Class(es)	8
Packing Group	III
Environmental Hazards	None
Special Precautions for User	None

International Maritime Dangerous Goods (IMDG)

UN Number	3265
UN Proper Shipping Name	Corrosive, Liquid, Acidic, Organic, N.O.S. (Alkylbenzenesulfonic acid)
UN Transport Hazard Class(es)	8
Packing Group	III
Environmental Hazards	None
Special Precautions for User	None

Page 14 of 16

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.16.2023

Revision date: 10.02.2023

Chem-Genie® 100

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN Number	3265
UN Proper Shipping Name	Corrosive, Liquid, Acidic, Organic, N.O.S. (Alkylbenzenesulfonic acid)
UN Transport Hazard Class(es)	8
Packing Group	III
Environmental Hazards	None
Special Precautions for User	None

SECTION 15: Regulatory Information

United States Regulations

Inventory Listing (TSCA): All ingredients are listed-active or exempt.

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed. **Export Notification under TSCA Section 12(b):** None of the ingredients are listed.

SARA Section 302 Extremely Hazardous Substances:

ii 302 Extremely Hazardous	Jubstances.	
Sulfuric acid		Listed
n 313 Toxic Chemicals:		
2-Butoxyethanol		Listed
Sulfuric acid		Listed
2-Butoxyethanol	Listed	N/A
Sulfuric acid	Listed	1000 lbs
Ethanol	Listed	100 lb
•	•	•
Ethanol	Listed	D001
(r) of the Clean Air Act (CAA)):	
Sulfuric acid		Listed
tts Right to Know:		
	Sulfuric acid n 313 Toxic Chemicals: 2-Butoxyethanol Sulfuric acid 2-Butoxyethanol Sulfuric acid Ethanol Ethanol Sulfuric acid Ethanol Sulfuric acid Ethanol	2-Butoxyethanol 2-Butoxyethanol 2-Butoxyethanol 2-Butoxyethanol Listed Sulfuric acid Listed Ethanol Listed Ethanol Ethanol Sulfuric acid Listed Sulfuric acid Listed

7664-93-9	Sulfuric acid	Listed
64-17-5	Ethanol	Listed
111-76-2	2-Butoxyethanol	Listed

New Jersey Right to Know:

7664-93-9	Sulfuric acid	Listed
64-17-5	Ethanol	Listed
111-76-2	2-Butoxyethanol	Listed

New York Right to Know:

7664-93-9	Sulfuric acid	Listed
64-17-5	Ethanol	Listed
111-76-2	2-Butoxyethanol	Listed

Pennsylvania Right to Know:

Page 15 of 16

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.16.2023 Page 16 of 16

Revision date: 10.02.2023

Chem-Genie® 100

7664-93-9	Sulfuric acid	Listed
64-17-5	Ethanol	Listed
111-76-2	2-Butoxyethanol	Listed

California Proposition 65:

▲ **WARNING:** This product can expose you to Strong inorganic acid mists containing sulfuric acid; which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Additional information: Not determined.

SECTION 16: Other Information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 0-0-0

Initial Preparation Date: 04.16.2023

Revision date: 10.02.2023

End of Safety Data Sheet