

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial Preparation Date:** 11.05.2021

Page 1 of 13

**Revision date:** 02.01.2022

4WD HI

### SECTION 1: Identification

#### Product Identifier

**Product Name:** 4WD HI

**Product code:** QW-0114

#### Recommended Use of the Product and Restriction on Use

**Relevant Identified Uses:** Alkaline detergent for cleaning/degreasing

**Uses Advised Against:** Not determined or not applicable.

**Reasons Why Uses Advised Against:** Not determined or not applicable.

#### Manufacturer or Supplier Details

##### Manufacturer:

##### United States

Quest Car Care Products

3333 Production Ct.

Zeeland, Michigan 49464

616-772-5100

www.questcarcare.com

#### Emergency Telephone Number:

##### United States

CHEMTREC

1-800-424-9300 (24 hrs)

1-800-262-8200 (24 hrs)

1-703-527-3887 (24 hrs (international))

### SECTION 2: Hazard(s) Identification

#### GHS Classification:

Corrosive to metals, category 1

Acute toxicity (oral), category 4

Skin corrosion, category 1A

Serious eye damage, category 1

Specific target organ toxicity - single exposure, category 2

#### Label elements

##### Hazard Pictograms:



**Signal Word:** Danger

#### Hazard statements:

H290 May be corrosive to metals

H314 Causes severe skin burns and eye damage

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 11.05.2021

Page 2 of 13

Revision date: 02.01.2022

## 4WD HI

H318 Causes serious eye damage  
H371 May cause damage to organs (inhalation, oral)  
H302 Harmful if swallowed

### Precautionary Statements:

P234 Keep only in original container  
P260 Do not breathe dust/fume/gas/mist/vapors/spray  
P264 Wash hands/skin thoroughly after contact with or handling.  
P280 Wear protective gloves/protective clothing/eye protection/face protection  
P270 Do not eat, drink or smoke when using this product  
P390 Absorb spillage to prevent material-damage  
P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P363 Wash contaminated clothing before reuse  
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
P310 Immediately call a POISON CENTER/911/PHYSICIAN IF: swallowed, eye contact, skin burns/rash or breathing difficulties.  
P321 Specific treatment (see first aid procedures on the product label in section 4 of this SDS)  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor/911.  
P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell  
P330 Rinse mouth  
P406 Store in corrosive resistant/or heavy duty plastic container using a chemical resistant inner liner.  
P405 Store locked up  
P501 Dispose of contents/container in accordance with local, state and federal regulations.

**Hazards Not Otherwise Classified:** None

## SECTION 3: Composition/Information on Ingredients

Identification	Name	Weight %
CAS Number: 1310-58-3	Potassium hydroxide	10-20
CAS Number: 111-76-2	2-Butoxyethanol	10-20
CAS Number: 141-43-5	2-aminoethanol	5-10

### Additional Information:

Ingredients not listed above are being withheld as trade secret.

## SECTION 4: First Aid Measures

### Description of First Aid Measures

#### General Notes:

Show this Safety Data Sheet to the doctor in attendance.  
Show this Safety Data Sheet to the doctor in attendance. Take precautions to ensure your own safety before attempting rescue. Wear appropriate safety eyewear, gloves, protective clothing and respiratory protection to prevent exposure. See Section 8 of this SDS for personal protective equipment

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 11.05.2021

Page 3 of 13

Revision date: 02.01.2022

4WD HI

recommendations. Do not use the mouth to mouth method if victim has ingested or inhaled the product. Give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper device.

## After Inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

## After Skin Contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

Treatment is urgent. Seek emergency medical treatment. Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse.

## After Eye Contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

Immediately rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. Seek immediate medical attention, preferably from an ophthalmologist.

Rinse eyes with plenty of water for several minutes. Remove contact lenses, if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

## After Swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. Seek immediate medical attention.

## Most Important Symptoms and Effects, Both Acute and Delayed

### Acute Symptoms and Effects:

Products that are corrosive to metals are often corrosive to the skin, eyes and the respiratory tract.

Exposure to skin may result in redness, pain, burning, inflammation and tissue damage. Exposure to eyes may result in irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision. Exposure via inhalation may result in cough, sore throat, burning sensation and shortness of breath. Exposure via ingestion may result in burns of the mouth and throat, abdominal pain, burning sensation in the throat and chest, nausea, vomiting, shock or collapse.

Eye contact may result in irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision.

May cause damage to organs. Effects are dependent on exposure (dose, concentration, contact time).

Acute oral exposure may lead to dizziness, drowsiness, headache, breathing difficulties, nausea, vomiting, abdominal pain, and lowering of consciousness. Adverse effects are dependent on exposure (dose, concentration, contact time).

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 11.05.2021

Page 4 of 13

Revision date: 02.01.2022

## 4WD HI

### Delayed Symptoms and Effects:

Effects are dependent on exposure (dose, concentration, contact time).  
Symptoms of exposure may be delayed.

### Immediate Medical Attention and Special Treatment

#### Specific Treatment:

In case of eye contact, seek prompt medical attention while rinsing is continued.  
If exhibiting symptoms of exposure, seek prompt medical attention.

#### Notes for the Doctor:

Treat symptomatically.

## SECTION 5: Firefighting Measures

### Extinguishing Media

#### Suitable Extinguishing Media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

#### Unsuitable Extinguishing Media:

Do not use water jet.

### Specific Hazards During Fire-Fighting:

Contact with metals may evolve flammable hydrogen gas. Thermal decomposition may produce irritating/toxic fumes/gases.

Thermal decomposition may produce irritating/toxic fumes/gases.

### Special Protective Equipment for Firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

### Special precautions:

DO NOT GET WATER INSIDE CONTAINERS. Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

## SECTION 6: Accidental Release Measures

### Personal Precautions, Protective Equipment, and Emergency Procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Do not get on skin, eyes or on clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling. Remove contaminated clothing and launder before reuse.

### Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

### Methods and Material for Containment and Cleaning Up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 11.05.2021

Page 5 of 13

Revision date: 02.01.2022

## 4WD HI

clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable corrosive resistant containers for future disposal. Do not get water in containers as reaction with water or moist air may release toxic, corrosive or flammable gases. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Harmful if swallowed. Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Avoid breathing dust, mist, fumes, vapors or spray. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

### Reference to Other Sections:

For personal protective equipment see Section 8. For disposal see Section 13.

## SECTION 7: Handling and Storage

### Precautions for Safe Handling:

Use appropriate personal protective equipment (see Section 8). Prevent skin contact. Do not get in eyes. Use only with adequate ventilation. Do not add water to the corrosive product. If it is necessary to mix a corrosive product with water, do so slowly adding the corrosive to cold water, in small amounts, and stir frequently. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use. Keep only in original packaging. Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Do not get in eyes. Avoid contact with skin and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

### Conditions for Safe Storage, Including Any Incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight and away from exit paths. Store in a corrosion-resistant container with a resistant inner liner. Inspect containers and storage area regularly for signs of leak and damage. Store containers at a convenient height for handling, below eye level if possible. High shelving increases the risk of dropping containers, personal injury and exposure. Ensure that appropriate fire fighting and spill-clean up equipment is readily available. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Store separately. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

## SECTION 8: Exposure Controls/Personal Protection

Only those substances with limit values have been included below.

### Occupational Exposure Limit Values:

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 11.05.2021

Page 6 of 13

Revision date: 02.01.2022

**4WD HI**

Country (Legal Basis)	Substance	Identifier	Permissible concentration
OSHA	2-Butoxyethanol	111-76-2	8-Hour TWA-PEL: 240 mg/m <sup>3</sup> (50 ppm [Table Z-1])
	2-Butoxyethanol	111-76-2	8-Hour TWA: 120 mg/m <sup>3</sup> (25 ppm [Table Z-1-A])
	Potassium hydroxide	1310-58-3	Ceiling Limit: 2 mg/m <sup>3</sup>
	2-aminoethanol	141-43-5	8-Hour TWA-PEL: 6 mg/m <sup>3</sup> (3 ppm)
NIOSH	2-Butoxyethanol	111-76-2	IDLH: 700 ppm
	2-Butoxyethanol	111-76-2	REL-TWA: 24 mg/m <sup>3</sup> (5 ppm [up to 10 hr])
	Potassium hydroxide	1310-58-3	Ceiling Limit: 2 mg/m <sup>3</sup>
	2-aminoethanol	141-43-5	REL-TWA: 8 mg/m <sup>3</sup> (3 ppm [up to 10 hr])
	2-aminoethanol	141-43-5	15-Minute STEL: 15 mg/m <sup>3</sup> (6 ppm)
	2-aminoethanol	141-43-5	IDLH: 30 ppm
ACGIH	2-Butoxyethanol	111-76-2	8-Hour TWA-PEL: 20 ppm
	Potassium hydroxide	1310-58-3	Ceiling Limit: 2 mg/m <sup>3</sup>
	2-aminoethanol	141-43-5	8-Hour TWA: 3 ppm
	2-aminoethanol	141-43-5	15-Minute STEL: 6 ppm
United States(California)	2-Butoxyethanol	111-76-2	8-Hour TWA-PEL: 97 mg/m <sup>3</sup> (20 ppm)
	2-Butoxyethanol	111-76-2	REL: 4700 ug/m <sup>3</sup> (Acute inhalation)
	2-Butoxyethanol	111-76-2	REL: 164 ug/m <sup>3</sup> (8-hour Inhalation)
	2-Butoxyethanol	111-76-2	REL: 82 ug/m <sup>3</sup> (Chronic inhalation)
	Potassium hydroxide	1310-58-3	Ceiling Limit: 2 mg/m <sup>3</sup>
	2-aminoethanol	141-43-5	8-Hour TWA-PEL: 8 mg/m <sup>3</sup> (3 ppm)
	2-aminoethanol	141-43-5	15-Minute STEL: 15 mg/m <sup>3</sup> (6 ppm)

### Biological Limit Values:

Country (Legal Basis)	Substance	Identifier	Determinant	Specimen	Sampling time	Permissible limits
ACGIH	2-Butoxyethanol	111-76-2	Butoxyacetic acid (with hydrolysis)	Creatinine in Urine	End of shift	200 mg/g

### Information on Monitoring Procedures:

Not determined or not applicable.

### Appropriate Engineering Controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

### Personal Protection Equipment

#### Eye and Face Protection:

Use safety glasses with side shields or goggles. Consider the use of a face shield for splash protection. Use eye protection equipment that has been tested and approved by recognized national standards (or

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 11.05.2021

Page 7 of 13

Revision date: 02.01.2022

## 4WD HI

equivalent).

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

### Skin and Body Protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Full body protection should be worn. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

### Respiratory Protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

### General Hygienic Measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

## SECTION 9: Physical and Chemical Properties

### Information on Basic Physical and Chemical Properties

<b>Appearance</b>	Yellow-neon green liquid
<b>Odor</b>	Amine, ether-like
<b>Odor threshold</b>	Not determined or not available.
<b>pH</b>	>13.0
<b>Melting point/freezing point</b>	Not determined or not available.
<b>Initial boiling point/range</b>	Not determined or not available.
<b>Flash point (closed cup)</b>	>93 c
<b>Evaporation rate</b>	Not determined or not available.
<b>Flammability (solid, gas)</b>	Not determined or not available.
<b>Upper flammability/explosive limit</b>	Not determined or not available.
<b>Lower flammability/explosive limit</b>	Not determined or not available.
<b>Vapor pressure</b>	Not determined or not available.
<b>Vapor density</b>	Not determined or not available.
<b>Density</b>	1.10-1.20
<b>Relative density</b>	Not determined or not available.



# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 11.05.2021

Page 8 of 13

Revision date: 02.01.2022

## 4WD HI

<b>Solubilities</b>	Water
<b>Partition coefficient (n-octanol/water)</b>	Not determined or not available.
<b>Auto/Self-ignition temperature</b>	Not determined or not available.
<b>Decomposition temperature</b>	Not determined or not available.
<b>Dynamic viscosity</b>	Not determined or not available.
<b>Kinematic viscosity</b>	Not determined or not available.
<b>Explosive properties</b>	Not determined or not available.
<b>Oxidizing properties</b>	Not determined or not available.

## SECTION 10: Stability and Reactivity

### Reactivity:

Not reactive under recommended handling and storage conditions.

### Chemical Stability:

Stable under recommended handling and storage conditions.

### Possibility of Hazardous Reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

### Conditions to Avoid:

Avoid generation of aerosols and mists, extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

### Incompatible Materials:

None known.

### Hazardous Decomposition Products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological Information

### Acute Toxicity

#### Assessment:

Harmful if swallowed.

**Product Data:** No data available.

#### Substance Data:

Name	Route	Result
2-Butoxyethanol	dermal	LD50 Rabbit: 220 mg/kg
	inhalation	LC50 Rat: 450 ppmV (4 hr - Vapor)
	Oral ATE	LD50 Rat: 1200 mg/kg (Annex VI to the CLP)
	oral	LD50 Rat: 470 mg/kg
Potassium hydroxide	oral	LD50 Rat: 273 mg/kg
2-aminoethanol	oral	LD50 Rat: 1089 mg/kg
	inhalation	LC50 Mouse: > 2420 mg/m <sup>3</sup> (2 hr)
	dermal	LD50 Rat: 1025 mg/kg

### Skin Corrosion/Irritation

#### Assessment:

Causes severe skin burns and eye damage.



# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 11.05.2021

Page 9 of 13

Revision date: 02.01.2022

4WD HI

## Product Data:

No data available.

## Substance Data:

Name	Result
2-Butoxyethanol	Causes skin irritation.
Potassium hydroxide	Causes severe skin burns.
2-aminoethanol	Causes severe skin burns.

## Serious Eye Damage/Irritation

### Assessment:

Causes serious eye damage.

### Product Data:

No data available.

### Substance Data:

Name	Result
2-Butoxyethanol	Causes serious eye irritation.
Potassium hydroxide	Causes serious eye damage.
2-aminoethanol	Causes serious eye damage.

## Respiratory or Skin Sensitization

**Assessment:** Based on available data, the classification criteria are not met.

### Product Data:

No data available.

**Substance Data:** No data available.

## Carcinogenicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product Data:** No data available.

**Substance Data:** No data available.

### International Agency for Research on Cancer (IARC):

Name	Classification
2-Butoxyethanol	Group 3
Potassium hydroxide	Not Applicable
2-aminoethanol	Not Applicable

### National Toxicology Program (NTP):

Name	Classification
2-Butoxyethanol	Not Applicable
Potassium hydroxide	Not Applicable
2-aminoethanol	Not Applicable

**OSHA Carcinogens:** Not applicable

## Germ Cell Mutagenicity

**Assessment:** Based on available data, the classification criteria are not met.

### Product Data:

No data available.

**Substance Data:** No data available.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 11.05.2021

Page 10 of 13

Revision date: 02.01.2022

## 4WD HI

### Reproductive Toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product Data:**

No data available.

**Substance Data:** No data available.

### Specific Target Organ Toxicity (Single Exposure)

**Assessment:**

May cause damage to organs.

**Product Data:**

No data available.

**Substance Data:**

Name	Result
2-aminoethanol	May cause respiratory irritation.

### Specific Target Organ Toxicity (Repeated Exposure)

**Assessment:** Based on available data, the classification criteria are not met.

**Product Data:**

No data available.

**Substance Data:** No data available.

### Aspiration toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product Data:**

No data available.

**Substance Data:** No data available.

### Information on Likely Routes of Exposure:

No data available.

### Symptoms Related to the Physical, Chemical, and Toxicological Characteristics:

No data available.

### Other Information:

No data available.

## SECTION 12: Ecological Information

### Acute (Short-Term) Toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product Data:** No data available.

**Substance Data:**

Name	Result
2-Butoxyethanol	Aquatic Invertebrates EC50 Daphnia magna: 1,550 mg/L (48 hr)
	Fish LC50 Oncorhynchus mykiss: 1,474 mg/L (96 hr)
2-aminoethanol	Fish LC50 Oncorhynchus mykiss: 105 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: 27.04 mg/L (48 hr)
	Aquatic Plants EC50 Phaeodactylum tricornutum: 24.7 mg/L (72 hr)

### Chronic (Long-Term) Toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product Data:** No data available.

**Substance Data:**

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 11.05.2021

Page 11 of 13

Revision date: 02.01.2022

## 4WD HI

Name	Result
2-Butoxyethanol	Fish NOEC Danio rerio: > 100 mg/L (21 d)
	Aquatic Invertebrates NOEC Daphnia magna: 100 mg/L (21 d)
2-aminoethanol	Fish NOEC Oryzias latipes: 1.24 mg/L (41 d)
	Aquatic Invertebrates NOEC Daphnia magna: 0.85 mg/L (21 d)
	Aquatic Plants NOEC Pseudokirchneriella subcapitata: 1 mg/L (72 hr)

### Persistence and Degradability

**Product Data:** No data available.

**Substance Data:**

Name	Result
2-Butoxyethanol	Readily biodegradable (90.4% degradation after 28 days).
Potassium hydroxide	The study on degradability does not need to be conducted as the substance is inorganic.
2-aminoethanol	Readily biodegradable (> 90% degradation after 21 days).

### Bioaccumulative Potential

**Product Data:** No data available.

**Substance Data:**

Name	Result
2-Butoxyethanol	Not expected to bioaccumulate (log Kow = 0.83).
Potassium hydroxide	Not expected to bioaccumulate, as it completely dissociates in water.
2-aminoethanol	Low bioaccumulation potential (calculated BCF: 9.2 L/kg).

### Mobility in Soil

**Product Data:** No data available.

**Substance Data:**

Name	Result
Potassium hydroxide	Low potential for adsorption. If emitted to surface water, sorption to sediment will be negligible.

### Results of PBT and vPvB assessment

**Product Data:**

**PBT assessment:** This product does not contain any substances that are assessed to be a PBT.

**vPvB assessment:** This product does not contain any substances that are assessed to be a vPvB.

**Substance Data:**

**PBT assessment:**

2-Butoxyethanol	This substance is not PBT.
Potassium hydroxide	The substance is not PBT.
2-aminoethanol	Substance is not PBT.

**vPvB assessment:**

2-Butoxyethanol	This substance is not vPvB.
Potassium hydroxide	The substance is not vPvB.
2-aminoethanol	Substance is not vPvB.

**Other Adverse Effects:** No data available.

## SECTION 13: Disposal Considerations

**Disposal Methods:**

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 11.05.2021

Page 12 of 13

Revision date: 02.01.2022

4WD HI


It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

### Contaminated packages:


Not determined or not applicable.

## SECTION 14: Transport Information


### United States Transportation of Dangerous Goods (49 CFR DOT)

UN Number	1760
UN Proper Shipping Name	Corrosive liquids, N.O.S. (Potassium Hydroxide, Monoethanolamine)
UN Transport Hazard Class(es)	8 
Packing Group	III
Environmental Hazards	None
Special Precautions for User	None

### International Maritime Dangerous Goods (IMDG)

UN Number	1760
UN Proper Shipping Name	Corrosive liquids, N.O.S. (Potassium Hydroxide, Monoethanolamine)
UN Transport Hazard Class(es)	8 
Packing Group	III
Environmental Hazards	None
Special Precautions for User	None

### International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN Number	1760
UN Proper Shipping Name	Corrosive liquids, N.O.S. (Potassium Hydroxide, Monoethanolamine)
UN Transport Hazard Class(es)	8 
Packing Group	III
Environmental Hazards	None
Special Precautions for User	None

## SECTION 15: Regulatory Information

### United States Regulations

**Inventory Listing (TSCA):** All ingredients are listed-active or exempt.

**Significant New Use Rule (TSCA Section 5):** None of the ingredients are listed.

**Export Notification under TSCA Section 12(b):** None of the ingredients are listed.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 11.05.2021

Page 13 of 13

Revision date: 02.01.2022

## 4WD HI

**SARA Section 302 Extremely Hazardous Substances:** None of the ingredients are listed.

**SARA Section 313 Toxic Chemicals:**

111-76-2	2-Butoxyethanol	Listed
----------	-----------------	--------

**CERCLA:**

111-76-2	2-Butoxyethanol	Listed	N/A
1310-58-3	Potassium hydroxide	Listed	1000 lb

**RCRA:** None of the ingredients are listed.

**Section 112(r) of the Clean Air Act (CAA):** None of the ingredients are listed.

**Massachusetts Right to Know:**

111-76-2	2-Butoxyethanol	Listed
1310-58-3	Potassium hydroxide	Listed
141-43-5	2-aminoethanol	Listed

**New Jersey Right to Know:**

111-76-2	2-Butoxyethanol	Listed
1310-58-3	Potassium hydroxide	Listed
141-43-5	2-aminoethanol	Listed

**New York Right to Know:**

111-76-2	2-Butoxyethanol	Listed
1310-58-3	Potassium hydroxide	Listed
141-43-5	2-aminoethanol	Listed

**Pennsylvania Right to Know:**

111-76-2	2-Butoxyethanol	Listed
1310-58-3	Potassium hydroxide	Listed
141-43-5	2-aminoethanol	Listed

**California Proposition 65:** None of the ingredients are listed.

**Additional information:** Not determined.

## SECTION 16: Other Information

**Abbreviations and Acronyms:** None

**Disclaimer:**

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**NFPA:** 0-0-0

**HMIS:** 3-0-0-X

**Initial Preparation Date:** 11.05.2021

**Revision date:** 02.01.2022

**End of Safety Data Sheet**