

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.01.2022

Page 1 of 15

Colormax Ceramic Foam Polish

SECTION 1: Identification

Product Identifier

Product Name: Colormax Ceramic Foam Polish

Recommended Use of the Product and Restriction on Use

Relevant Identified Uses: Foaming Polish-Sealant for Commercial Car Washing

Uses Advised Against: Not determined or not applicable.

Reasons Why Uses Advised Against: Not determined or not applicable.

Manufacturer or Supplier Details

Manufacturer:

United States

Quest Car Care Products

3333 Production Ct.

Zeeland, Michigan 49464

616-772-5100

www.questcarcare.com

Emergency Telephone Number:

United States

CHEMTREC

1-800-424-9300 (24 hrs)

1-800-262-8200 (24 hrs)

1-703-527-3887 (24 hrs (international))

SECTION 2: Hazard(s) Identification

GHS Classification:

Acute toxicity (oral), category 4

Skin irritation, category 2

Serious eye damage, category 1

Reproductive toxicity, category 2

Specific target organ toxicity - single exposure, category 2

Label elements

Hazard Pictograms:



Signal Word: Danger

Hazard statements:

H315 Causes skin irritation

H318 Causes serious eye damage

H361 Suspected of damaging fertility or the unborn child (oral)

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.01.2022

Page 2 of 15

Colormax Ceramic Foam Polish

H371 May cause damage to organs (oral)

H302 Harmful if swallowed

Precautionary Statements:

P264 Wash hands/skin thoroughly after contact with or handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection

P201 Obtain special instructions before use

P202 Do not handle until all safety precautions have been read and understood

P260 Do not breathe dust/fume/gas/mist/vapors/spray

P270 Do not eat, drink or smoke when using this product

P302+P352 IF ON SKIN: WASH WITH PLENTY OF SOAP AND WATER.

P321 Specific treatment (see first aid procedures on the product label in section 4 of this SDS)

P332+P313 If skin irritation occurs: Get medical advice/attention

P362 Take off contaminated clothing and wash it before reuse

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 Immediately call a POISON CENTER/911/PHYSICIAN IF: swallowed, eye contact, skin burns/rash or breathing difficulties.

P308+P313 IF exposed or concerned: Get medical advice/attention

P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor/911.

P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

P330 Rinse mouth

P405 Store locked up

P501 Dispose of contents/container in accordance with local, state and federal regulations.

Hazards Not Otherwise Classified: None

SECTION 3: Composition/Information on Ingredients

Identification	Name	Weight %
CAS Number: 1643-20-5	Dodecyldimethylamine oxide	10-15
CAS Number: 111-76-2	2-Butoxyethanol	10-15
CAS Number: Proprietary	Cationic surfactant	1-5
CAS Number: 3332-27-2	N,N-dimethyltetradecylamine N-oxide	1-5
CAS Number: Proprietary	Dimethyl Siloxanes-Silanes	1-5
CAS Number: 64-19-7	Acetic Acid	1-5
CAS Number: 556-67-2	Octamethylcyclotetrasiloxane	0.1-1
CAS Number: 67-56-1	Methanol	0.05-0.1

Additional Information:

Ingredients not listed above are being withheld as trade secret.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.01.2022

Page 3 of 15

Colormax Ceramic Foam Polish

SECTION 4: First Aid Measures

Description of First Aid Measures

General Notes:

Show this Safety Data Sheet to the doctor in attendance.

Show this Safety Data Sheet to the doctor in attendance. Take precautions to ensure your own safety before attempting rescue. Wear appropriate safety eyewear, gloves, protective clothing and respiratory protection to prevent exposure. See Section 8 of this SDS for personal protective equipment recommendations. Do not use the mouth to mouth method if victim has ingested or inhaled the product. Give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper device.

After Inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

After Skin Contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

After Eye Contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

Immediately rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. Seek immediate medical attention, preferably from an ophthalmologist.

Rinse eyes with plenty of water for several minutes. Remove contact lenses, if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

After Swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most Important Symptoms and Effects, Both Acute and Delayed

Acute Symptoms and Effects:

Skin contact may result in redness, pain, burning and inflammation.

Eye contact may result in irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision.

May cause damage to organs. Effects are dependent on exposure (dose, concentration, contact time).

Acute oral exposure may lead to dizziness, drowsiness, headache, breathing difficulties, nausea, vomiting, abdominal pain, and lowering of consciousness. Adverse effects are dependent on exposure (dose, concentration, contact time).

Delayed Symptoms and Effects:

Effects are dependent on exposure (dose, concentration, contact time).

Long term exposure may affect fertility. Symptoms include, but are not limited to: menstrual problems, altered sexual behavior/fertility/ and pregnancy outcome. Long term exposure may also affect development of the unborn child. Symptoms include, but are not limited to: intrauterine growth

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.01.2022

Page 4 of 15

Colormax Ceramic Foam Polish

retardation, pre-term birth, birth defects and postnatal death.

Symptoms of exposure may be delayed.

Immediate Medical Attention and Special Treatment

Specific Treatment:

In case of eye contact, seek prompt medical attention while rinsing is continued.

If exhibiting symptoms of exposure, seek prompt medical attention.

Notes for the Doctor:

Treat symptomatically.

SECTION 5: Firefighting Measures

Extinguishing Media

Suitable Extinguishing Media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Unsuitable Extinguishing Media:

Do not use water jet.

Specific Hazards During Fire-Fighting:

Thermal decomposition may produce irritating/toxic fumes/gases.

Special Protective Equipment for Firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts.

Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers.

Avoid unnecessary run-off of extinguishing media which may cause pollution.

SECTION 6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Do not get on skin, eyes or on clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling. Remove contaminated clothing and laundry before reuse.

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways.

Discharge into the environment must be avoided.

Methods and Material for Containment and Cleaning Up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Harmful if swallowed. Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Avoid breathing dust, mist, fumes, vapors or spray. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to Other Sections:

For personal protective equipment see Section 8. For disposal see Section 13.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.01.2022

Page 5 of 15

Colormax Ceramic Foam Polish

SECTION 7: Handling and Storage

Precautions for Safe Handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Do not get in eyes. Avoid contact with skin and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for Safe Storage, Including Any Incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure Controls/Personal Protection

Only those substances with limit values have been included below.

Occupational Exposure Limit Values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
OSHA	2-Butoxyethanol	111-76-2	8-Hour TWA-PEL: 240 mg/m ³ (50 ppm [Table Z-1])
	2-Butoxyethanol	111-76-2	8-Hour TWA: 120 mg/m ³ (25 ppm [Table Z-1-A])
	Acetic Acid	64-19-7	8-Hour TWA-PEL: 25 mg/m ³ (10 ppm)
	Methanol	67-56-1	8-Hour TWA-PEL: 260 mg/m ³ (200 ppm)
	Methanol	67-56-1	15-Minute STEL: 325 mg/m ³ (250 ppm)
NIOSH	2-Butoxyethanol	111-76-2	IDLH: 700 ppm
	2-Butoxyethanol	111-76-2	REL-TWA: 24 mg/m ³ (5 ppm [up to 10 hr])
	Acetic Acid	64-19-7	REL: 25 mg/m ³ (10 ppm [for up to a 10-hour workday during a 40-hour workweek])
	Acetic Acid	64-19-7	STEL: 37 mg/m ³ (15 ppm)
	Acetic Acid	64-19-7	IDLH: 50 ppm
	Methanol	67-56-1	REL-TWA: 260 mg/m ³ (200 ppm [for up to a 10-hour workday during a 40-hour workweek])
	Methanol	67-56-1	15-Minute STEL: 325 mg/m ³ (250 ppm)
	Methanol	67-56-1	IDLH: 6000 ppm
ACGIH	2-Butoxyethanol	111-76-2	8-Hour TWA-PEL: 20 ppm
	Acetic Acid	64-19-7	TLV-TWA: 10 ppm (8 hr)
	Acetic Acid	64-19-7	15-Minute STEL: 15 ppm
	Methanol	67-56-1	8-Hour TWA: 200 ppm
	Methanol	67-56-1	15-Minute STEL: 250 ppm

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.01.2022

Page 6 of 15

Colormax Ceramic Foam Polish

Country (Legal Basis)	Substance	Identifier	Permissible concentration
United States(California)	2-Butoxyethanol	111-76-2	8-Hour TWA-PEL: 97 mg/m ³ (20 ppm)
	2-Butoxyethanol	111-76-2	REL: 4700 ug/m ³ (Acute inhalation)
	2-Butoxyethanol	111-76-2	REL: 164 ug/m ³ (8-hour Inhalation)
	2-Butoxyethanol	111-76-2	REL: 82 ug/m ³ (Chronic inhalation)
	Acetic Acid	64-19-7	8-Hour TWA: 25 mg/m ³ (10 ppm)
	Acetic Acid	64-19-7	15-Minute STEL: 37 mg/m ³ (15 ppm)
	Acetic Acid	64-19-7	Ceiling Limit: 40 ppm
	Methanol	67-56-1	15-Minute STEL: 325 mg/m ³ (250 ppm)
	Methanol	67-56-1	PEL Ceiling: 1000 ppm
	Methanol	67-56-1	8-Hour TWA: 260 mg/m ³ (200 ppm)
WEEL	Octamethylcyclotetrasiloxane	556-67-2	8-Hour TWA: 10 ppm

Biological Limit Values:

Country (Legal Basis)	Substance	Identifier	Determinant	Specimen	Sampling time	Permissible limits
ACGIH	2-Butoxyethanol	111-76-2	Butoxyacetic acid (with hydrolysis)	Creatinine in Urine	End of shift	200 mg/g
	Methanol	67-56-1	Methanol	Urine	End of Shift	15 mg/L
	Methanol	67-56-1	Methanol	Urine	End of shift.	15 mg/L

Information on Monitoring Procedures:

Not determined or not applicable.

Appropriate Engineering Controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal Protection Equipment

Eye and Face Protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Use safety glasses with side shields or goggles. Consider the use of a face shield for splash protection.

Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and Body Protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.01.2022

Page 7 of 15

Colormax Ceramic Foam Polish

prior to use. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Full body protection should be worn. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory Protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

General Hygienic Measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and Chemical Properties

Information on Basic Physical and Chemical Properties

Appearance	Red, Blue, Green, Purple, Yellow
Odor	Fruity, etherlike
Odor threshold	Not determined or not available.
pH	4.0-6.0
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	70-90 c
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	0.97-1.00
Solubilities	Water
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

SECTION 10: Stability and Reactivity

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.01.2022

Page 8 of 15

Colormax Ceramic Foam Polish

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical Stability:

Stable under recommended handling and storage conditions.

Possibility of Hazardous Reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to Avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Incompatible Materials:

None known.

Hazardous Decomposition Products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological Information

Acute Toxicity

Assessment:

Harmful if swallowed.

Product Data: No data available.

Substance Data:

Name	Route	Result
2-Butoxyethanol	dermal	LD50 Rabbit: 220 mg/kg
	inhalation	LC50 Rat: 450 ppmV (4 hr - Vapor)
	Oral ATE	LD50 Rat: 1200 mg/kg (Annex VI to the CLP)
	oral	LD50 Rat: 470 mg/kg
Acetic Acid	oral	LD50 rat: 3310 mg/kg
	inhalation	LC50 rat: 11.4 mg/L (4 hr [vapor])
Dodecyldimethylamine oxide	oral	LD50 Rat: 1064 mg/kg
	dermal	LD50 Rat: > 2000 mg/kg
N,N-dimethyltetradecylamine N-oxide	oral	LD50 Rat: 1495 mg/kg
Octamethylcyclotetrasiloxane	oral	LD50 Rat: > 4800 mg/kg
	dermal	LD50 Rat: > 2375 mg/kg
	inhalation	LC50 Rat: 36 mg/L (4 hr [aerosol])
Methanol	Oral ATE	LD50 Rat: 100 mg/kg
	Dermal ATE	LD50 Rabbit: 300 mg/kg
	Inhalation ATE	LC50 Rat: 3 mg/L (4 hr)
	oral	LD50 Rat: 5628 mg/kg
	dermal	LD50 Rabbit: 15,800 mg/kg
	inhalation	LC50 Rat: 64,000 ppmV (4 hr)

Skin Corrosion/Irritation

Assessment:

Causes skin irritation.

Product Data:

No data available.

Substance Data:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.01.2022

Page 9 of 15

Colormax Ceramic Foam Polish

Name	Result
2-Butoxyethanol	Causes skin irritation.
Acetic Acid	Causes severe skin burns.
Cationic surfactant	Causes skin irritation.
Dodecyldimethylamine oxide	Causes skin irritation.
N,N-dimethyltetradecylamine N-oxide	Causes skin irritation.
Dimethyl Siloxanes-Silanes	Causes skin irritation.

Serious Eye Damage/Irritation

Assessment:

Causes serious eye damage.

Product Data:

No data available.

Substance Data:

Name	Result
2-Butoxyethanol	Causes serious eye irritation.
Acetic Acid	Causes serious eye damage.
Cationic surfactant	Causes serious eye irritation.
Dodecyldimethylamine oxide	Causes serious eye damage.
N,N-dimethyltetradecylamine N-oxide	Causes serious eye damage.
Dimethyl Siloxanes-Silanes	Causes serious eye irritation.

Respiratory or Skin Sensitization

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data: No data available.

International Agency for Research on Cancer (IARC):

Name	Classification
2-Butoxyethanol	Group 3
Acetic Acid	Not Applicable
Cationic surfactant	Not Applicable
Dodecyldimethylamine oxide	Not Applicable
N,N-dimethyltetradecylamine N-oxide	Not Applicable
Octamethylcyclotetrasiloxane	Not Applicable
Methanol	Not Applicable
Dimethyl Siloxanes-Silanes	Not Applicable

National Toxicology Program (NTP):

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.01.2022

Page 10 of 15

Colormax Ceramic Foam Polish

Name	Classification
2-Butoxyethanol	Not Applicable
Acetic Acid	Not Applicable
Cationic surfactant	Not Applicable
Dodecyldimethylamine oxide	Not Applicable
N,N-dimethyltetradecylamine N-oxide	Not Applicable
Octamethylcyclotetrasiloxane	Not Applicable
Methanol	Not Applicable
Dimethyl Siloxanes-Silanes	Not Applicable

OSHA Carcinogens: Not applicable

Germ Cell Mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Reproductive Toxicity

Assessment:

Suspected of damaging fertility or the unborn child.

Product Data:

No data available.

Substance Data:

Name	Result
Octamethylcyclotetrasiloxane	Suspected of damaging fertility.

Specific Target Organ Toxicity (Single Exposure)

Assessment:

May cause damage to organs.

Product Data:

No data available.

Substance Data:

Name	Result
Methanol	Causes damage to Optic nerve (nervus opticus), central nervous system.

Specific Target Organ Toxicity (Repeated Exposure)

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Information on Likely Routes of Exposure:

No data available.

Symptoms Related to the Physical, Chemical, and Toxicological Characteristics:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.01.2022

Page 11 of 15

Colormax Ceramic Foam Polish

No data available.

Other Information:

No data available.

SECTION 12: Ecological Information

Acute (Short-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result
2-Butoxyethanol	Aquatic Invertebrates EC50 Daphnia magna: 1,550 mg/L (48 hr)
	Fish LC50 Oncorhynchus mykiss: 1,474 mg/L (96 hr)
Acetic Acid	Fish LC50 Oncorhynchus mykiss: > 300.82 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: > 300.82 mg/L (48 hr)
	Aquatic Plants EC50 Skeletonema costatum: > 300.82 mg/L (72 hr)
Dodecyldimethylamine oxide	Aquatic Plants EC50 Pseudokirchneriella subcapitata: 0.07 mg/L (72 hr)
Octamethylcyclotetrasiloxane	Aquatic Plants EC50 Pseudokirchneriella subcapitata: > 0.022 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: > 0.015 mg/L (48 hr)
	Fish LC50 Oncorhynchus mykiss: > 0.022 mg/L (96 hr)

Chronic (Long-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result
2-Butoxyethanol	Fish NOEC Danio rerio: > 100 mg/L (21 d)
	Aquatic Invertebrates NOEC Daphnia magna: 100 mg/L (21 d)
Dodecyldimethylamine oxide	Aquatic Invertebrates NOEC Daphnia magna: 0.7 mg/L (21 d)
	Fish NOEC Pimephales promelas: 0.495 mg/L (15 d)
Octamethylcyclotetrasiloxane	Fish NOEC Oncorhynchus mykiss: \geq 0.0044 mg/L (93 d)
	Aquatic Invertebrates NOEC Daphnia magna: \geq 0.015 mg/L (21 d)
	Aquatic Plants NOEC Pseudokirchneriella subcapitata: < 0.022 mg/L (96 hr)

Persistence and Degradability

Product Data: No data available.

Substance Data:

Name	Result
2-Butoxyethanol	Readily biodegradable (90.4% degradation after 28 days).
Acetic Acid	This substance is readily biodegradable in water (96% degradation seen in non-acclimated freshwater study after 20 days).
Dodecyldimethylamine oxide	Readily biodegradable in water (95% degradation [CO ₂ evolution] in 28 days).
N,N-dimethyltetradecylamine N-oxide	This substance is readily biodegradable.
Octamethylcyclotetrasiloxane	Under test conditions, little biodegradation observed (3.7% biodegradation [CO ₂ evolution] after 29 days).
Methanol	Readily biodegradable (97% degradation after 20 days).

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.01.2022

Page 12 of 15

Colormax Ceramic Foam Polish

Bioaccumulative Potential

Product Data: No data available.

Substance Data:

Name	Result
2-Butoxyethanol	Not expected to bioaccumulate (log Kow = 0.83).
Acetic Acid	Accumulation in organisms is not to be expected (BCF: 3.16 dimensionless).
Dodecyldimethylamine oxide	Substance has low potential for bioaccumulation (log kow: <3; estimated BCF: 0.7).
N,N-dimethyltetradecylamine N-oxide	This substance has low potential for bioaccumulation.
Octamethylcyclotetrasiloxane	Substance is expected to bioaccumulate (BCF: 12,400 L/kg).
Methanol	Methanol does not significantly bioaccumulate in fish. Experimental BCFs of < 10 in fish species.

Mobility in Soil

Product Data: No data available.

Substance Data:

Name	Result
Acetic Acid	This substance is highly mobile; therefore, adsorption to soil is not expected (Koc: 1.153, QSAR).
Dodecyldimethylamine oxide	Substance is expected to be slightly mobile (log Koc: 3.18).
N,N-dimethyltetradecylamine N-oxide	This substance has low potential to be adsorbed by the soil/sediment.
Octamethylcyclotetrasiloxane	Substance is hardly mobile (log Koc: 4.22); therefore, adsorption to soil is expected.
Methanol	Highly mobile (Koc: 0.13 - 0.61 dimensionless).

Results of PBT and vPvB assessment

Product Data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT.

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

Substance Data:

PBT assessment:

2-Butoxyethanol	This substance is not PBT.
Acetic Acid	This substance is not PBT.
Dodecyldimethylamine oxide	The substance is not PBT.
N,N-dimethyltetradecylamine N-oxide	This substance is not PBT.
Octamethylcyclotetrasiloxane	Substance is PBT.
Methanol	This substance is not PBT.

vPvB assessment:

2-Butoxyethanol	This substance is not vPvB.
Acetic Acid	This substance is not vPvB.
Dodecyldimethylamine oxide	The substance is not vPvB.
N,N-dimethyltetradecylamine N-oxide	This substance is not vPvB.
Octamethylcyclotetrasiloxane	Substance is vPvB.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.01.2022

Page 13 of 15

Colormax Ceramic Foam Polish

Methanol

This substance is not vPvB.

Other Adverse Effects: No data available.

SECTION 13: Disposal Considerations

Disposal Methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

Contaminated packages:

Not determined or not applicable.

SECTION 14: Transport Information

United States Transportation of Dangerous Goods (49 CFR DOT)

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

International Maritime Dangerous Goods (IMDG)

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

SECTION 15: Regulatory Information

United States Regulations

Inventory Listing (TSCA): All ingredients are listed-active or exempt.

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export Notification under TSCA Section 12(b):

111-76-2	2-Butoxyethanol	Not Listed
----------	-----------------	------------

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.01.2022

Page 14 of 15

Colormax Ceramic Foam Polish

64-19-7	Acetic Acid	Not Listed
Proprietary	Cationic surfactant	Not Listed
1643-20-5	Dodecyldimethylamine oxide	Not Listed
3332-27-2	N,N-dimethyltetradecylamine N-oxide	Not Listed
556-67-2	Octamethylcyclotetrasiloxane	Listed
67-56-1	Methanol	Not Listed
Proprietary	Dimethyl Siloxanes-Silanes	Not Listed

SARA Section 302 Extremely Hazardous Substances: None of the ingredients are listed.

SARA Section 313 Toxic Chemicals:

111-76-2	2-Butoxyethanol	Listed
67-56-1	Methanol	Listed

CERCLA:

111-76-2	2-Butoxyethanol	Listed	N/A
64-19-7	Acetic Acid	Listed	5000
67-56-1	Methanol	Listed	5000 lbs

RCRA:

67-56-1	Methanol	Listed	U154
---------	----------	--------	------

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know:

111-76-2	2-Butoxyethanol	Listed
64-19-7	Acetic Acid	Listed
67-56-1	Methanol	Listed

New Jersey Right to Know:

111-76-2	2-Butoxyethanol	Listed
64-19-7	Acetic Acid	Listed
67-56-1	Methanol	Listed

New York Right to Know:

111-76-2	2-Butoxyethanol	Listed
64-19-7	Acetic Acid	Listed
67-56-1	Methanol	Listed

Pennsylvania Right to Know:

111-76-2	2-Butoxyethanol	Listed
64-19-7	Acetic Acid	Listed
67-56-1	Methanol	Listed

California Proposition 65:

⚠️WARNING: This product can expose you to Methanol; which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Additional information: Not determined.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.01.2022

Page 15 of 15

Colormax Ceramic Foam Polish

SECTION 16: Other Information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 0-0-0

HMIS: 1-1-0-B

Initial Preparation Date: 02.01.2022

End of Safety Data Sheet