

SAFETY DATA SHEET



Prepared to GHS-USA Requirements

OUTSHINE 80 FD

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

TRADE NAME: OUTSHINE 80-FD **DATE PREPARED:** 6/1/17
SUPERCEDES: 10/1/14

Product Type: Solvent Based Tire & Vinyl Shine
Recommended Use: Vehicle Detailing

Supplier: QUEST CAR CARE PRODUCTS
3333 PRODUCTION CT
ZEELAND, MI. 49464

Phone: 1-616-772-5100
Fax: 1-616-931-3173

EMERGENCY INFORMATION: CHEMTREC: 1-800-424-9300 (24 HOUR RESPONSE)

SECTION 2: HAZARD(S) IDENTIFICATION

*** EMERGENCY OVERVIEW ***:

Extremely flammable liquid and vapor. May be fatal or cause blindness if swallowed. May be fatal if inhaled; can cause permanent injury to the eyes!

Symbol(s) of Product



Signal Word:

Danger

GHS HAZARD CLASSIFICATION:

Flammable Liquid, category 2
Acute Toxicity, Oral, category 3
Skin Irritation, category 2
STOT, single exposure, category 3, RT1
STOT, single exposure, category 3, NE
Reproductive Toxicity, category 2
STOT, single exposure, category 2
STOT, repeated exposure, category 2

GHS HAZARD STATEMENT:

H225 Highly flammable liquid and vapor.
H301 Toxic if swallowed.
H315 Causes skin irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H371 May cause damage to organs.
H373 May cause damage to organs through prolonged or repeated exposure.

GHS PRECAUTIONARY STATEMENTS

P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.

SAFETY DATA SHEET



Prepared to GHS-USA Requirements

OUTSHINE 80 FD

P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician
P302+P352	IF ON SKIN: Wash with plenty of soap and water
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P311	IF exposed or concerned: Call a POISON CENTER/doctor/physician
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER/doctor/physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No.	Wt. %
N-Hexane	110-54-3	60-100
Polydimethylsiloxane	63148-62-9	

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

SECTION 4: FIRST AID MEASURES

IF IN EYES:

Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly. Remove contact lenses if worn.

IF ON SKIN:

Immediately flush skin with plenty of water. Remove clothing. Get medical attention immediately. Wash clothing separately and clean shoes before reuse.

IF INHALED:

Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention. To prevent aspiration, keep head below knees.

IF INGESTED:

Call a physician or poison control center immediately. Only induce vomiting at the instruction of medical personnel. Never give anything by mouth to an unconscious person.

SECTION 5: FIRE FIGHTING MEASURES

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Extremely flammable liquid and vapor. May cause flash fire or explosion. Vapors can travel to a source of ignition and flash back. Empty containers retain product residue (liquid and/or vapor) and can be dangerous.

DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. Also, do not reuse container without commercial cleaning or reconditioning.

SPECIAL FIREFIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Avoid use of solid water streams. Use water with caution. Material will float and may ignite on surface of water. Water may be ineffective in fighting the fire. Water spray to cool containers or protect personnel. Use with caution. Use water spray to knock down vapors. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

SAFETY DATA SHEET



Prepared to GHS-USA Requirements

OUTSHINE 80 FD

SECTION 6: ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.) Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. A vapor suppressing foam may be used to reduce vapors. Collect spilled materials for disposal. Use only non-combustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Remove from surface by skimming or with suitable absorbents. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Recover by pumping (use an explosion proof or hand pump).

SECTION 7: HANDLING AND STORAGE

HANDLING: Use only in a well-ventilated area. Avoid breathing vapor, fumes or mist. Avoid contact with eyes, skin, and clothing. Take precautionary measures against static discharge. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Always open containers slowly to allow any excess pressure to vent. Follow all MSDS/label precautions even after containers are emptied because they may retain product residues.

STORAGE: Keep away from heat, sparks, and flame. Containers can build up pressure if exposed to heat (fire). Store containers in a cool, well ventilated place. Keep container closed when not in use. Protect from direct sunlight. Static Discharge, materials can accumulate static charges which can cause an incendiary electrical discharge. Material is a static accumulator which has the potential of forming ignitable vapor-air mixtures in storage tanks.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Ingredients with Occupational Exposure Limits

Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	OSHA PEL-TWA	OSHA PEL-CEILING
N-Hexane	50 ppm	N.D.	500 ppm	N.D.

PERSONAL PROTECTION:

RESPIRATORY PROTECTION:

In well ventilated areas none is normally required. If using in a confined space wear a NIOSH approved (or equivalent) full-face piece airline respirator in the positive pressure mode with emergency escape provisions.

SKIN PROTECTION:

Wear impervious gloves to prevent contact with the skin. Wear long sleeves when contact is likely to occur. Wear protective gear as needed - apron, suit, boots.

EYE PROTECTION:

Wear safety glasses with side shields (or goggles) and a face shield.

OTHER PROTECTIVE EQUIPMENT:

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

HYGENIC PRACTICES:

Do not eat, drink, or smoke in areas where this material is used. Avoid breathing vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating.

SAFETY DATA SHEET



Prepared to GHS-USA Requirements

OUTSHINE 80 FD

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Color: Blue

Odor: Gas like / Grape Background

Density, g/cm³: 0.71-0.74

Freeze Point, °F: -75

Solubility in Water: Insoluble

Boiling Range, °F: 147 - 392

Evaporation Rate: Not determined

Vapor Density: N.D.

Physical State: Liquid

Odor Threshold: N.D.

pH: N/A

Viscosity: N.D.

Explosive Limits, vol%: 1.2 - 36.0

Flash Point, °F: 0

Auto-ignition Temp., °F: N.D.

Vapor Pressure: N.D.

SECTION 10: STABILITY AND REACTIVITY

STABILITY: No Information

CONDITIONS TO AVOID: Avoid impact, friction, heat, sparks, flame and source of ignition.

INCOMPATIBILITY: Keep separate from alkalis. Avoid contact with hydrogen peroxide, chromic anhydride, nitric acid, mixed nitric/sulfuric acid, nitrosyl perchlorate, permonosulfuric acids, potassium tert-butoxide, sodium hypobromite, chlorinated melamine. Prevent contact with strong oxidizing agents. Keep away from acids.

HAZARDOUS DECOMPOSITION PRODUCTS: Toxic gases/fumes are given off during burning or thermal decomposition. During combustion carbon monoxide may be formed. During combustion carbon dioxide may be formed. Decomposition releases nitrogen oxides. Thermal decomposition upon exposure to air may produce silicone oxides. Combustion can lead to the formation of formaldehyde. Combustion can lead to formation of formic acid.

HAZARDOUS POLYMERIZATION: No Information

SECTION 11: TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS:

EFFECTS OF OVEREXPOSURE - INHALATION: May be fatal if inhaled. Inhalation of high solvent vapor or mist concentrations can cause coma and death. Vapors can cause irritation of the respiratory tract. High concentrations can cause headache, nausea, weakness, lightheadedness, and stupor (CNS depression). Overexposure may cause lung damage. May cause dizziness and drowsiness. May cause peripheral nervous system disorder and/or damage.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Causes skin irritation. Skin absorption may add significantly to the overall toxic effect. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Causes eye irritation. Symptoms may include stinging, tearing, redness and swelling.

EFFECTS OF OVEREXPOSURE - INGESTION: May be fatal or cause blindness if swallowed. Harmful or fatal if liquid is aspirated into lungs. Irritating to mouth, throat, and stomach. Can be readily absorbed by the stomach and intestinal tract. Symptoms include burning sensation of the mouth and esophagus, nausea, vomiting, diarrhea, dizziness, staggering gait, drowsiness, loss of consciousness and delirium as well as additional central nervous system effects.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Material is slowly eliminated from the body, therefore it can have cumulative toxicity effects with repeated exposures. Possible brain damage from overexposure. Overexposure may cause nervous system damage. May cause delayed lung damage. Significant exposure to this chemical may adversely affect people with chronic disease of the respiratory system, central nervous system, kidney, liver, skin, and/or eyes.

SAFETY DATA SHEET



Prepared to GHS-USA Requirements

OUTSHINE 80 FD

Primary Route(s) of Entry: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Name according to EEC	Oral LD50	Dermal LD50	Vapor LC50
110-54-3	N-Hexane	5000	>2000	>3367

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No Information

SECTION 13: DISPOSAL CONSIDERATIONS

*****Always dispose of any waste in accordance with all local, state, and federal regulations.**

DISPOSAL METHOD: Dispose of waste in accordance with all local, state and federal regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section). Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways as product will float on water. Ventilate spill area and stay upwind of the spill. A vapor suppressing foam may be used to reduce vapors. Collect spilled materials for disposal. Use only non-combustible material(s) for clean-up. Use clean, non-sparking tools to collect absorbed materials. Remove from surface by skimming or with suitable absorbents. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Recover by pumping (use an explosion proof or hand pump).

SECTION 14: TRANSPORT INFORMATION

DOT UN/NA Number:	UN1208
DOT Proper Shipping Name:	Hexanes
Packing Group:	II
DOT Hazard Class:	3
Hazard Sub-Class:	No Information

SECTION 15: REGULATORY INFORMATION

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories: Fire Hazard, Acute Health Hazard, Chronic Health Hazard.

SAFETY DATA SHEET



Prepared to GHS-USA Requirements

OUTSHINE 80 FD

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372.

Chemical Name	CAS-No.
N-Hexane	110-54-3

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States: No TSCA components exist in this product.

U.S. State Regulations:

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical Name	CAS-No.
Polydimethylsiloxane:	63148-62-9

PENNSYLVANIA RIGHT-TO-KNOW:

The following non-hazardous ingredients are present in the product are at or greater than 3%.

Chemical Name	CAS-No.
Polydimethylsiloxane:	63148-62-9

CALIFORNIA PROPOSITION 65 CARCINOGENS:

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

No Proposition 65 Carcinogens exist in this product.

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS:

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

Chemical Name	CAS-No.
None	

International Regulations: As follows

CANADIAN WHMIS:

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class: No Information

SECTION 16: OTHER INFORMATION

HMIS Ratings:

Health: 2

Flammability: 3

Reactivity: 0

Personal Protection: X

Volatile Organic Compounds: 563 g/L

DISCLAIMER: THE VOLATILE ORGANIC COMPOUND (VOC) CONTENT REPORTED HEREIN, IF ANY, IS BASED ON A MATERIAL VOC CALCULATION. NOTE THAT SEVERAL METHODS ARE USED FOR CALCULATING VOC CONTENT AND THAT STANDARDS/ REQUIREMENTS REGARDING VOC CONTENT VARY BY LOCATION/JURISDICTION. ACCORDINGLY, EMCO MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, REGARDING THIS MATERIAL'S COMPLIANCE WITH VOC STANDARDS/REQUIREMENTS APPLICABLE IN LOCATIONS/JURISDICTIONS WHERE THIS MATERIAL MAY BE SOLD OR USED.

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information on this SDS was obtained from sources which we believe to be reliable. However, the information provided is without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the product itself. The information and recommendations are offered for the user's consideration and examination and should be used to make an independent determination of the methods to safeguard workers and the environment. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For these reasons we do not assume responsibility and expressly disclaim any liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this MSDS may not be applicable. It is the responsibility of the user to comply with all local, state or federal regulations.